

フジパーライト保温材 厚さ表

〈パイプカバー(普通品)〉

口 径		配管外径 (mm)	厚 さ (mm)					
A	B		30	40	50	65	75	100
15	1/2	22	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
20	3/4	27	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
25	1	34	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
32	1,1/4	43	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
40	1,1/2	49	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
50	2	61	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
65	2,1/2	76	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
80	3	89	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)
90	3,1/2	102	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	
100	4	114	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)
125	5	140	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	○ (3)
150	6	165	○ (2)	○ (2)	○ (2)	○ (2)	○ (2)	○ (4)
175	7	191	○ (2)	○ (2)	○ (2)			
200	8	216	○ (3)	○ (3)	○ (3)	○ (4)	○ (4)	○ (4)
225	9	242	○ (4)	○ (4)	○ (4)			
250	10	267	○ (4)	○ (4)	○ (4)	○ (4)	○ (4)	○ (5)
300	12	319	○ (5)	○ (4)	○ (5)	○ (5)	○ (5)	○ (5)
350	14	356	○ (5)	○ (5)	○ (5)	○ (5)	○ (5)	○ (6)
400	16	406	○ (6)	○ (6)	○ (6)	○ (6)	○ (6)	○ (6)
450	18	457	○ (6)	○ (6)	○ (6)	○ (6)	○ (6)	○ (7)
500	20	508	○ (6)	○ (7)	○ (7)	○ (7)	○ (7)	○ (7)
550	22	559	○ (7)	○ (8)	○ (7)	○ (8)	○ (8)	○ (8)
600	24	610	○ (7)	○ (7)	○ (7)	○ (8)	○ (8)	○ (8)
650	26	661	○ (8)	○ (8)	○ (8)	○ (8)	○ (8)	○ (9)
700	28	711	○ (10)	○ (10)	○ (9)	○ (9)	○ (9)	○ (9)
750	30	762	○ (10)		○ (9)		○ (9)	
800	32	813			○ (10)		○ (10)	

- 長さは全て610mmです。(許容差はJIS A 9510を参照)
- 保温厚さが100mmを超える場合は、2層になります。
- ()内数は円周に対する割り数です。